



TAPER BORE PULLEYS



SPC

PART NO	dr	b ₂	BUSH NO	d ₃	d ₂ max	L	PULLEY CONFIG NO	K	d ₁	d
200 X 3	200	85	2517		60	45	5	20	144	210.2
200 X 4	200	110.5	3020		75	51	5	29.5	144	210.2
200 X 5	200	136	3535		90	89	5	23.5	144	210.2
200 X 6	200	161.5	3535		90	89	5	36	144	210.2
200 X 8	200	212.5	3535		90	89	5	46	144	210.2
212 X 3	212	85	3020		75	51	5	17	156	222.2
212 X 4	212	110.5	3020		75	51	5	29.5	156	222.2
212 X 5	212	136	3535		90	89	5	23.5	156	222.2
212 X 6	212	161.5	3535		90	89	5	36	156	222.2
212 X 8	212	212.5	3535		90	89	5	46	156	222.2
224 X 3	224	85	3020		75	51	5	17	173	234.2
224 X 4	224	110.5	3535		90	89	5	11	173	234.2
224 X 5	224	136	3535		90	89	5	23.5	168	234.2
224 X 6	224	161.5	3535		90	89	5	36	173	234.2
224 X 8	224	212.5	3535		90	89	5	46	168	234.2
236 X 3	236	85	3020		75	51	5	17	180	246.2
236 X 4	236	110.5	3535		90	89	5	11	184	246.2
236 X 5	236	136	3535		90	89	5	23.5	180	246.2
236 X 6	236	161.5	3535		90	89	5	36	184	246.2
236 X 8	236	212.5	3535		90	89	5	46	180	246.2
250 X 3	250	85	3020		75	51	5	17	194	260.2
250 X 4	250	110.5	3535		90	89	5	11	198	260.2
250 X 5	250	136	3535		90	89	5	23.5	194	260.2
250 X 6	250	161.5	3535		90	89	5	36	198	260.2
250 X 8	250	212.5	3535		90	89	5	62	198	260.2
265 X 3	265	85	3535	175	90	89	2			275.2
265 X 4	265	110.5	3535		90	89	5	11	209	275.2
265 X 5	265	136	3535		90	89	5	23.5	209	275.2
265 X 6	265	161.5	3535		90	89	5	36.0	209	275.2
265 X 8	265	212.5	3535		90	89	5	62	209	275.2
280 X 3	280	85	3535	175	90	89	2			290.2


TAPER BORE PULLEYS



SPC

PART NO	dr	b ₂	BUSH NO	d ₃	d ₂ max	L	PULLEY CONFIG NO	K	d ₁	d
280 X 4	280	110.5	3535	175	90	89	7	11	228	290.2
280 X 5	280	136	3535		90	89	5	23.5	224	290.2
280 X 6	280	161.5	3535	175	90	89	7	36	228	290.2
280 X 8	280	212.5	3535		90	89	5	62	228	290.2
300 X 3	300	85	3535	175	90	89	8	2	247	310.2
300 X 4	300	110.5	3535	175	90	89	7	11	244	310.2
300 X 5	300	136	3535	175	90	89	7	23.5	247	310.2
300 X 6	300	161.5	3535	175	90	89	7	36	247	310.2
300 X 8	300	212.5	4040	0	100	102	5	55.0	244	310.2
315 X 3	315	85	3535	175	90	89	8	2	264	325.2
315 X 4	315	110.5	3535	175	90	89	7	11	264	325.2
315 X 5	315	136	3535	175	90	89	7	23.5	259	325.2
315 X 6	315	161.5	3535	175	90	89	7	36	259	325.2
315 X 8	315	212.5	4040	0	100	102	5	55.0	259	325.2
355 X 3	355	85	3535	175	90	89	8	2	304	365.2
355 X 4	355	110.5	3535	175	90	89	7	11	299	365.2
355 X 5	355	136	3535	175	90	89	7	23.5	304	365.2
355 X 6	355	161.5	3535	175	90	89	7	36	304	365.2
355 X 8	355	212.5	4040	210	100	102	7	55.0	304	365.2
375 X 3	375	85	3535	175	90	89	8	2	319	385.2
375 X 4	375	110.5	3535	175	90	89	7	11	324	385.2
375 X 5	375	136	3535	175	90	89	7	23.5	324	385.2
375 X 6	375	161.5	4040	210	100	102	7	30	319	385.2
375 X 8	375	212.5	4545	240	110	114	7	49	324	385.2
400 X 3	400	85	3535	175	90	89	8	2	344	410.2
400 X 4	400	110.5	3535	175	90	89	7	11	348	410.2
400 X 5	400	136	3535	175	90	89	7	23.5	344	410.2
400 X 6	400	161.5	4040	210	100	102	7	30	344	410.2
400 X 8	400	212.5	4545	240	110	114	7	49	348	410.2
425 X 3	425	85	3535	175	90	89	10	2	395	435.2
425 X 4	425	110.5	3535	175	90	89	9	11	394	435.2

TAPER BORE PULLEYS



SPC

PART NO	dr	b ₂	BUSH NO	d ₃	d ₂ max	L	PULLEY CONFIG NO	K	d ₁	d
425 X 5	425	136	3535	175	90	89	9	23.5	370	435.2
425 X 6	425	161.5	4040	210	100	102	9	30	370	435.2
425 X 8	425	212.5	4545	240	110	114	9	49	370	435.2
450 X 3	450	85	3535	175	90	89	10	2	395	460.2
450 X 4	450	110.5	3535	175	90	89	9	11	394	460.2
450 X 5	450	136	4040	210	100	102	9	17	394	460.2
450 X 6	450	161.5	4545	240	110	114	9	24	395	460.2
450 X 8	450	212.5	5050	265	125	127	9	43	395	460.2
475 X 3	475	85	3535	175	90	89	10	2	419	485.2
475 X 4	475	110.5	3535	175	90	89	9	11	419	485.2
475 X 5	475	136	4040	210	100	102	9	17	419	485.2
475 X 6	475	161.5	4545	240	110	114	9	24	419	485.2
475 X 8	475	212.5	5050	265	125	127	9	43	419	485.2
500 X 3	500	85	3535	175	90	85	10	2	444	510.2
500 X 4	500	110.5	3535	175	90	85	9	11	444	510.2
500 X 5	500	136	4040	210	100	102	9	17	444	510.2
500 X 6	500	161.5	4545	240	110	114	9	24	445	510.2
500 X 8	500	212.5	5050	265	125	127	9	43	445	510.2
530 X 3	530	85	3535	175	90	89	10	2	474	540.2
530 X 4	530	110.5	4040	210	100	102	9	4.0	474	540.2
530 X 5	530	136	4040	210	100	102	9	17	474	540.2
530 X 6	530	161.5	4545	240	110	114	9	24	475	540.2
530 X 8	530	212.5	5050	265	125	127	9	43	474	540.2
560 X 3	560	85	3535	175	90	89	10	2	504	570.2
560 X 4	560	110.5	4040	210	100	102	9	4.0	504	570.2
560 X 5	560	136	4545	240	110	114	9	11	505	570.2
560 X 6	560	161.5	5050	265	125	127	9	17	505	570.2
560 X 8	560	212.5	5050	265	125	127	9	43	505	570.2
630 X 3	630	85	4040	210	100	102	10	2	574	640.2
630 X 4	630	110.5	4545	240	110	114	10	1.5	574	640.2
630 X 5	630	136	5050	265	125	127	9	4.5	574	640.2

[illegible]